



SWITCHBACK CREEK  
at Sun Peaks

# OVERHEAD DOORS

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 5/23/2024

Project: Switch Back Creek BLD A- unit 1

Section: Div 8 overhead doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

  
Dan Valiquette

## Construction

### L11000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### L12000

#### Double-Layer: Steel + Insulation


- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### L13138/L13000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Dollars
- Extra Quiet Operation



## Specifications

	AMARR LINCOLN L11000	AMARR LINCOLN L12000	AMARR LINCOLN L13138	AMARR LINCOLN L13000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION*</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		0.32	0.27	0.23
<b>R-VALUE†</b>		6.54	6.48	9.05
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION‡</b>			•	•
<b>WIND LOAD‡ AVAILABLE</b>	•	•	•	•
<b>PAINT FINISH WARRANTY*</b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY*</b>	1 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 5/23/2024

Project: Switch Back Creek BLD A- unit 2

Section: Div 8 overhead doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

  
Dan Valiquette

## Construction

### L11000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### L12000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### L13138/L13000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation



## Specifications

	AMARR LINCOLN L11000	AMARR LINCOLN L12000	AMARR LINCOLN L13138	AMARR LINCOLN L13000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION*</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		0.32	0.27	0.23
<b>R-VALUE†</b>		5.64	6.48	9.05
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION‡</b>			•	•
<b>WIND LOAD‡ AVAILABLE</b>	•	•	•	•
<b>PAINT FINISH WARRANTY*</b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY*</b>	1 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 0/19/2024

Project: Switch Back Creek BLD A unit 3

Section: Div 8 Overhead Doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

  
Dan Valiquette

# Amarr® Lincoln

## Construction

### LI1000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### LI2000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### LI3138/LI3000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation

#### LI3138 - 1-3/8"



#### LI3000 - 2"



## Specifications

	AMARR LINCOLN LI1000	AMARR LINCOLN LI2000	AMARR LINCOLN LI2138	AMARR LINCOLN LI3000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION*</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		0.32	0.27	0.23
<b>R-VALUE<sup>2</sup></b>		5.64	6.48	9.05
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION<sup>1</sup></b>			•	•
<b>WIND LOAD<sup>3</sup> AVAILABLE</b>	•	•	•	•
<b>PAINT FINISH WARRANTY<sup>4</sup></b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY<sup>5</sup></b>	1 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 6/19/2024

Project: Switch Back Creek BLD A Unit 4

Section: Div 8 Overhead Doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

  
Dan Valiquette



## Construction

### LI1000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### LI2000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



U-factor  
**.32**

### LI3138/LI3000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation

#### LI3138 - 1-3/8"



U-factor  
**.27**

#### LI3000 - 2"



U-factor  
**.23**

## Specifications

	AMARR LINCOLN LI1000	AMARR LINCOLN LI2000	AMARR LINCOLN LI3138	AMARR LINCOLN LI3000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION*</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		<b>0.32</b>	<b>0.27</b>	<b>0.23</b>
<b>R-VALUE*</b>		5.64	6.48	9.05
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION†</b>			•	•
<b>WIND LOAD‡ AVAILABLE</b>	•	•	•	•
<b>PAINT FINISH WARRANTY*</b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY*</b>	3 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 7/22/2024


Project: Switch Back Creek BLD B Unit 5

Section: Div 8 Overhead Doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

  
Dan Valiquette

## Construction

### LI1000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### LI2000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### LI3138/LI3000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation



## Specifications

	AMARR LINCOLN LI1000	AMARR LINCOLN LI2000	AMARR LINCOLN LI3138	AMARR LINCOLN LI3000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION*</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		0.32	0.27	0.23
<b>R-VALUE*</b>		5.64	4.48	9.05
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION†</b>			•	•
<b>WIND LOAD‡ AVAILABLE</b>			•	•
<b>PAINT FINISH WARRANTY*</b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY*</b>	1 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 7/22/2024

Project: Switch Back Creek BLD B unit 6

Section: Div 8 Overhead Doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

Dan Valiquette



## Construction

### L11000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### L12000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### L13138/L13000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation

#### L13138 - 1-3/8"



#### L13000 - 2"



## Specifications

	AMARR LINCOLN L11000	AMARR LINCOLN L12000	AMARR LINCOLN L13138	AMARR LINCOLN L13000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
<b>Ribbed</b>			•	•
<b>INSULATION*</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		0.32	0.27	0.23
<b>R-VALUE<sup>†</sup></b>		4.54	4.48	9.25
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION<sup>‡</sup></b>			•	•
<b>WIND LOAD<sup>§</sup> AVAILABLE</b>			•	•
<b>PAINT FINISH WARRANTY*</b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY*</b>	1 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 9/9/2024

Project: Switch Back Creek BLD B unit 7

Section: Div 8 Overhead Doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

Dan Valiquette



## Construction

### LI1000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### LI2000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### LI3138/LI3000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation



## Specifications

	AMARR LINCOLN LI1000	AMARR LINCOLN LI2000	AMARR LINCOLN LI3138	AMARR LINCOLN LI3000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION</b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR</b>		0.32	0.27	0.23
<b>R-VALUE</b>		5.64	6.48	9.05
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION*</b>			•	•
<b>WIND LOAD* AVAILABLE</b>	•	•	•	•
<b>PAINT FINISH WARRANTY*</b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY*</b>	1 Year	2 Years	3 Years	3 Years

**DOOR SYSTEMS KAMLOOPS**

1365 B Dalhousie Dr.  
Kamloops, BC V2C 5P4  
Tel: 250-374-5655 Fax: 250-828-1054

---

Date: 9/9/2024

Project: Switch Back Creek BLD B unit 8

Section: Div 8 Overhead Doors

**GUARANTEE:**

All materials are guaranteed from any defects from the use of materials, deficiencies of design strength or by reason of poor workmanship which may appear within one year(s) from the date of substantial performance.

**DOOR SYSTEMS KAMLOOPS**

  
Dan Valiquette



# Amarr® Lincoln

## Construction

### L11000

#### Single-Layer: Steel

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance



### L12000

#### Double-Layer: Steel + Insulation

- Heavy-duty Exterior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation with Vinyl Backing
- Energy Efficient
- Quiet Operation



### L13138/L13000

#### Triple-Layer: Steel + Insulation + Steel

- Heavy-duty Exterior and Interior Steel
- Durable, Reliable, Low Maintenance
- Environmentally Safe Polystyrene Thermal Insulation
- Two Energy Efficiency Options
- Extra Quiet Operation



## Specifications

	AMARR LINCOLN L11000	AMARR LINCOLN L12000	AMARR LINCOLN L13138	AMARR LINCOLN L13000
<b>PANEL DESIGNS</b>				
Short	•	•	•	•
Long	•	•	•	•
Flush (Steel Embossment)	Stucco	Stucco	Woodgrain	Woodgrain
Ribbed			•	•
<b>INSULATION<sup>1</sup></b>		Polystyrene	Polystyrene	Polystyrene
<b>U-FACTOR<sup>2</sup></b>		0.32	0.27	0.23
<b>R-VALUE<sup>2</sup></b>		3.64	4.48	9.25
<b>DOOR THICKNESS</b>	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)
<b>STEEL THICKNESS</b>	25 ga	25 ga	27/27 ga	27/27 ga
<b>INSULATED GLASS OPTION<sup>3</sup></b>			•	•
<b>WIND LOAD<sup>3</sup> AVAILABLE</b>			•	•
<b>PAINT FINISH WARRANTY<sup>4</sup></b>	15 Years	25 Years	Lifetime	Lifetime
<b>WORKMANSHIP/HARDWARE WARRANTY<sup>5</sup></b>	1 Year	2 Years	3 Years	3 Years